



Cutting & Bending Machines for concrete reinforcing steel bars
 Via Achille Grandi - 20056 Trezzo s/Adda (MI) - ITALY
 Phone: +39.2.90.93.97.35 - Fax: +39.2.90.93.97.78
 Mailto: info@simpedit.it - http://www.simpedit.it

CUTTING MACHINE MOD. C56 EVO 3-PHASE



| | |
|-----------------------|-------------------|
| <i>Measures</i> | : 117 x 65 x 92 h |
| <i>Weight</i> | : 640 kg |
| <i>Oil</i> | : 3 kg |
| <i>Electric Motor</i> | : 7,5 Hp – 5,5kW |
| <i>Rpm</i> | : 37 rpm |

| Cutting capability | R. = 65 Kg. / mm ² | | | R. = 85 Kg. / mm ² | | |
|--------------------|-------------------------------|--------|--------|-------------------------------|--------|--------|
| | 1 Ø 48 | 2 Ø 34 | 3 Ø 26 | 1 Ø 42 | 2 Ø 32 | 3 Ø 24 |

STANDARD EQUIPMENT

- 1 set composed of 2 blades, already fitted on machine
- This special Screw Locator can easily be regulated according to the bar diameter and quantity to be cut. The Screw Locator permits a perfect alignment of one or more bars against the blade and an exact perpendicular cut.
- Centralized lubrication system. Thanks to the new construction system, the parts that need lubrication are now easily reached through a unique lubricating point.
- Mechanical lever and pedal.
- Magnetothermic switch

*****TECHNICAL DATA*****

- Completely new projected machine body in mono block made of **Spheroid Cast Iron**;
- Gearing in cemented steel;
- Reinforced mechanical parts for a better resistance and performance of the machine;
- Increased cutting capacity;
- Equipped with screw locator for bars alignment.



SCREW LOCATOR



LUBRICATING SYSTEM

